

PR80

PROXIMITY READER



The PR80 is a high performance proximity card reader for access control applications. Its sleek, modern contoured design makes it one of the slimmest readers in its class. A variety of de facto interface standards are supported for compatibility with most popular card access controllers in the market today.



Technical specifications

Reading range	: Up to 10cm
Operating Frequency	: 125Khz EM compatible
Input voltage	: 9 to 15 VDC
Current Drawn	: 80mA @12V
Operating Temp.	: -20 to 60°C
LED indicator	: Tri colours (Red, Green, Amber)
Colours Available	: Beige or Black
Output Formats	: * Wiegand (26, 36 & 44bits) * ABA ISO Track 2 * EIA RS-485
Finishing	: Weatherproof, Epoxy potting
Dimensions (mm)	: 100H X 60W X 12D

Output Formats	Colours Available	
	Beige	Black
Wiegand 44 bit interface	PR80-W44BG	PR80-W44BK
Wiegand 26 bit interface	PR80-W26BG	PR80-W26BK
Wiegand 36 bit interface	PR80-W36BG	PR80-W36BK
ABA ISO Track 2 emulation	PR80-AT2BG	PR80-AT2BK
Serial EIA RS-485 ASCII output	PR80-A485BG	PR80-S485BK

The logo and the trade name SIERRA is the trademark of Sierra Technology (M) Sdn Bhd. Certain product names mentioned herein may be trade names and/or registered trademarks of other companies. The specifications contained herein are subject to change without notice.

Copyright © 1993, 2002 Sierra Technology (M) Sdn Bhd

Sierra Technology (M) Sdn. Bhd. (Company No. 267857-U)

27, Jalan SS 25/41, Mayang Industrial Park, 47301 Petaling Jaya, Selangor D. E., Malaysia.

Tel: (603) 7806-3966 Fax: (603) 7806-3900 Homepage: <http://www.sierra.com.my>